

TPD-01-BT



Bluetooth printer TPD-01-BT

Mobilize your business

TPD-01-BT Bluetooth connectivity



Technical data

Mobilize your printer with bluetooth!

- The multifunctional thermal paper printer TPD-01 now comes with a bluetooth interface
- Mobilize your business and print additional information from your mobile device onto your taximeter printer
- Easy implementation
- For Android operated Smartphones or Tablets
- Comes with Android libraries and demo program
- Existing printers are simply upgraded by a software update and exchange of the printed circuit board for keypad.

TPD-01-BT prints out:

- Trip receipts
- Shift accountings
- Trip memory
- Utilisation figures
- or any data from your android application

Various mounting possibilities:

- ▶ 3 different mounting versions for the paper roll: upside, backwards or completely on the back side
- ▶ Various mounting possibilities of the printer itself: velcro mounting, mounting bracket 90° or 30°
- ▶ For Mercedes Benz E211 and E212 mounting holder instead of ash-tray

Convincing Technology

Low current consumption corresponds to the automotive standards. The HALE TPD-01-BT consumes current only during printing (automatic wake-up via interface) and is otherwise in sleep mode.



Printer also available with magnetic card reader

HALE electronic GmbH
Eugen-Müller-Straße 18
A-5020 Salzburg

T: +43-662/439011-0 E: marketing@hale.at www.hale.at

Approvals



Dimensions	115 x 57 x 30 mm (4.53 x 224 x 1.18 inch) (W x H x D)
Weight	180 g
Operating voltage	8-18 V
Current consumption	 typ. 2 mA in stand-by [< 7 mA with bluetooth] typ. 350 A in sleep mode with CAN operation (< 5 mA with bluetooth) max. 1.5 A with 12V
Temperature	 -25°C to +85°C, -13°F to + 185°F (stock) -10°C to + 70°C, +14°F to + 158°F (operation)
Resolution	300 dpi, 28 characters / line
Graphics	32 kB bitmaps
Fast print	up to 4 cm, 1.58 inch / sec.
Special features	 3-coloured status LED autosleep and wake-up end of paper detection printer hed protection 2 operating keys
Interfaces	Bluetooth class 2 • RS 232 (5V) for Microtax®-05, WSZ-05 • interfaces for connection of data dispatching • devices and credit card terminals • baud rates 300/1200/9600 baud [opt. 4800 baud] • HALE CAN for Microtax®-06, SPT-01,

SPT-02 • opt. or integrated magnetic card reader



8